

NON-METALLIC HAZARDOUS LOCATION C1D2, C2D2

IR1-4-2-26-UNV-T8 IR1-4-3-26-UNV-T8
IR1-4-2-46-UNV-T5HO IR1-4-3-46-UNV-T5HO

4-FT., 2-3LAMP, T8 (32-watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE
4-FT., 2-3-LAMP, T5HO (54-watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE



FIXTURE FEATURES

Intended Use

Intended for hazardous location applications:

- Class I, Div. 2-Groups A, B, C, D
- Class II Div. II – Groups F,G

Designed for applications requiring corrosion resistant fixtures. Excellent for marine wet and damp locations. Inside of fixture is drip-proof. Typical applications include solvent and cleaning areas, petrochemical facilities, marine facilities, waste treatment plants and food processing applications.

Construction

- Housing is non-metallic glass reinforced polyester. Gasket is poured in-place. Latches are stainless steel locking type. Diffuser is high impact acrylic
- Surface mounting brackets are standard with fixture.

Listings

UL 1598-A – Outdoor Marine Type (salt water) UL 844 – Class I, Div 2, A,B,C,D, C2D2, F, G
Meets Coast Guard Specifications

Approximate Fixture Dimensions

Length: 52-inches
Width: 7 5/8-inches
Height: 5 1/4-inches

Mounting

Fixture can be surface mounted or suspended.

Warranty

Fixture is warranted for five years from delivery date against manufacturing defects. Ballast warranty is provided through the ballast manufacturer.

NON-METALLIC HAZARDOUS LOCATION C1D2, C2D2

IR1-4-2-26-UNV-T8

IR1-4-3-26-UNV-T8

IR1-4-2-46-UNV-T5HO

IR1-4-3-46-UNV-T5HO



Ballast

Energy efficient, 120-277 multi-volt, electronic, automatic resetting, program start (T5HO) and instant start (T8) ballasts are standard in all fixtures. Emergency Ballasts are available.

Lamps

Comes in 2 and 3 lamp versions of T8 and T5. For ordering please refer to the below part numbers. For emergency ballast add – EM to end of part number.

IR1-4-2-26-UNV-T8 = 2 lamp T8

IR1-4-2-46-UNV-T5 = 2 lamp T5

IR1-4-3-26-UNV-T8 = 3 lamp T8

IR1-4-3-46-UNV-T5 = 3 lamp T5

Dimensions

<p>A= 6 3/4” B= 5 1/4” C= 7 5/8 “ D= 36 9/16 “ E= 52”</p>

