

BROKEN ARROW, OK 1-866-860-6399

EXPLOSION-PROOF FLUORESCENT

IR4-4-2-46-UNV-T5HO 2 Tube 2 lamp IR4-4-2-46-UNV-T5HO 2 Tube 4 lamp IR4-4-4-46-UNV-T5HO 4 Tube 4 lamp

4-FT., 2-LAMP, 2 TUBE T5HO (54 watt), FLUORESCENT EXPLOSION-PROOF FIXTURE 4-FT., 4-LAMP, 2 TUBE T5HO (54 watt), FLUORESCENT EXPLION-PROOF FIXTURE 4-FT., 4-LAMP, 4 TUBE T5HO (54 watt), FLUORESCENT EXPLOSION-PROOF FIXTURE



FIXTURE FEATURES

Intended Use

Intended for explosion-proof applications:

- Class I. Div. 1-Groups C & D
- Class II, Div, 1 & 2 Groups E,F,G

Typical application would include solvent and cleaning areas, paint spray booths, oil and gas drilling applications, aircraft maintenance, chemical manufacturing, waste treatment plants, oil and gas refining and processing.

Construction

Extruded aluminum housing and clear glass lamp enclosures. End mounting brackets are standard with fixture.

Ballast

Energy efficient, 120-277 multi-volt, electronic, automatic resetting, program start T5HO ballasts a Emergency ballasts available (Indicate EM on order)

Listings

UL 595 – Outdoor Marine Type (salt water)
UL 844
UL 924
UL 1598 Marine Type
Paint Spray Booth Approved

Approximate Fixture Dimensions & Weights

4-ft., 2-lamp & 4 Lamp
Length: 52-inches
Width: 11.3-inches
Height: 8.5-inches
Weight: 65 lbs

4-ft., 4-lamp
Length: 52-inches
Width: 24-inches
Height: 9.5-inches
Weight: 120 lbs

Mounting

Fixture can be surface mounted or suspended.

Warranty

Fixture is warranted for five years from delivery date against manufacturing defects. Ballast warranty is provided through the ballast manufacturer.

Accessories

- Wire Guard
- Safety Cable
- Shock Mount




BROKEN ARROW, OK 1-866-860-6399

EXPLOSION-PROOF FLUORESCENT

IR4-4-2-46-UNV-T5HO 2 Tube 2 lamp IR4-4-4-2-46-UNV-T5HO 2 Tube 4 lamp IR4-4-4-6-UNV-T5HO 4 Tube 4 lamp



Dimensions



NOMINAL LENGTH	LENGTH INCHES	WIDTH	HEIGHT	WEIGHT
2 FOOT 2 TUBE	27.5	11.25	8.5	55
4 FOOT 2TUBE	52	11.25	8.5	65
4 FOOT 4 TUBE	52.5	24	9.5	120